



15 WATT SINGLE & DUAL OUTPUT

Regulated, 4:1 Input Range DC/DC Converters



FEATURES

- **4:1 Wide Input Range**
- **Industry Standard Package & Pinout**
- **Efficiency to 83% @ FL**
- **500 Vdc Input/ Output Isolation**
- **6 Sided Shielding**
- **On/Off Control**
- **Output Trim**

Y15 Series

Specifications

All specifications are typical at nominal input, full load, and 25°C , unless otherwise noted.

INPUT

Input Voltages.....	Voltage Range
12 Vdc.....	9-36 Vdc
24 Vdc.....	18-72 Vdc
Input Filter.....	Pi Network

OUTPUT

Voltage Accuracy	
+Vout.....	±1.5%
-Vout.....	± 2.0%
Line Regulation	±1.0% max.
Load Regulation.....	± 0.5% (Single), ± 2.0% (Dual)
Ripple Noise (20 MHz BW).....	1% Vout p-p max.
Temperature Coefficient (at FL).....	± 0.02%/°C max
Transient Response.....	20ms max.

GENERAL

Efficiency.....	86% typical
Isolation Voltage.....	500 Vdc min.
Isolation Resistance.....	1000MOhms
Switching Frequency.....	100KHz
Protection.....	Over Voltage
.....	Fold Back Short Circuit Protection

ENVIRONMENTAL

Operating Temperature Range.....	-25 to +71°C
Storage Temperature Range.....	-55 to +105°C
Cooling.....	Free Air Convection
EMI/RFI.....	Six Sided Continuous Metal Shield

PHYSICAL

Case Material.....	Black Coated Copper w/ Non-Conductive Metal Base
Weight.....	3 oz. (9 grams)
Dimensions.....	2.00" x 2.00" x 0.45"
.....	50.8 x 50.8 x 11.43mm

Selection Guide

(Continued)

	Input Voltage Nominal (Range) (Vdc)	Output Voltage (Vdc)	Output Current (mA)	Model Number	Case
SINGLE OUTPUT	12 (9-36)	5	3000	Y15-24S5	B2
		12	1250	Y15-24S12	B2
		15	1000	Y15-24S15	B2
	48 (18-72)	5	3000	Y15-48S5	B2
		12	1250	Y15-48S12	B2
		15	1000	Y15-48S15	B2
DUAL	12 (9-36)	±12	±625	Y15-12-12	B2
		±15	±500	Y15-12-15	B2
	48 (18-72)	±12	±625	Y15-48-12	B2
		±15	±500	Y15-48-15	B2

Available in 2.6" X 3.0" X 0.82" package (Case JY)
Use suffix JY after model number.


Mechanical Specifications

I/O Connections		
Pin	SINGLE	DUAL
1	+Vin	+Vin
2	-Vin	-Vin
3	+Vout	+Vout
4	TRIM	Common
5	-Vout	-Vout
6	ON/OFF	ON/OFF

I/O Connections		
Pin	SINGLE	DUAL
1	+Vin	+Vin
2	-Vin	-Vin
3	No Pin	+Vout
4	Trim	Common
5	No Pin	-Vout
6	+Vout	No Pin
7	-Vout	No Pin
8	ON/OFF	ON/OFF


*Pin 6 optional. Use suffix "RE" after model number.

Case B2



All Dimensions are in inches (mm)

Case JY



All Dimensions are in inches (mm)

POLYTRON DEVICES, Inc.

P.O. Box 398, Paterson, New Jersey 07544 U.S.A.
Tel: (973)345-5885 Fax: (973)345-1264 • Email: sales@polytrondevices.com • www.polytrondevices.com